
Pyure Insight[™] Edge 1101 Gateway, with HMI

The Pyure Insight™ Edge 1101 Gateway with HMI handles all secure network communications. The gateway comes in an enclosure with an exterior touchscreen display (HMI) on the front cover. It is typically installed in a clean, conditioned space and at an appropriate height to access the HMI function.

Specifications

opecine delons	
Dimensions (LxWxD)	16.9" x 14.7" x 8.0" (429 mm x 373 mm x 203 mm)
Weight	15.6 lbs (7.1 kg)
Shipping Dimensions	20.0" x 18.0" x 12.0" (508 mm x 457 mm x 305 mm)
Shipping Weight	18.0 lb (8.7 kg)
Voltage options	90 - 246 VAC @50/60Hz
Power	120 Watts
Units	All Pyure controlled products
Sensor	Supports PoE and analog
Temperature range	50° to 122° F (10° to 50° C)
Gateway Certification	CE, EN, FCC, IEC, RCM, REACH, RoHS, UKCA, VCCI, WEEE
Warranty	2 years covering defects in workmanship or materials
Communications Protocols	RJ45 Ethernet (TCP/IP, IPX, Modbus TCP, CIP) RS-485, USB

Dimensions of Pyure Insight Edge 1101 Gateway, with HMI.



Product Numbers

00819355022397	Pyure Insight™ Edge 1101 - Gateway with HMI
	[INEXX17]

